

**Description**

inner diameter: 0.859", thickness 0.139", preformed packing, hydrocarbon fuel resistant, MS29513 series o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS29513212
Minimum Qty (MOQ):	25
NSN:	5331-00-250-0226
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS29513-212 Specifications

<b>Outside Diameter:</b>	1.119 Inches Minimum And 1.155 Inches Maximum
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	0.853 Inches Minimum And 0.865 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-212](https://military-fasteners.com/o_rings/o_rings/MS29513-212) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.