



Military-Fasteners.com

P/N MS29513-214

Description

inner diameter: 0.984", thickness 0.139", preformed packing, hydrocarbon fuel resistant, MS29513 series o-ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513214
Minimum Qty (MOQ):	50
NSN:	5331-00-250-0232
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS29513-214 Specifications

Outside Diameter:	1.262 Inches Nominal
Temp Rating:	-65.0 Deg Fahrenheit And 200.0 Deg Fahrenheit
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	0.978 Inches Minimum And 0.990 Inches Maximum
Elongation Percentage:	200 Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-214 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.