

Description

inner diameter: 1.046", thickness 0.139", preformed packing, hydrocarbon fuel resistant, MS29513 series oring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513215
Minimum Qty (MOQ):	25
NSN:	5331-00-250-0235
Schedule B:	4016.93.5010
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS29513-215 Specifications

Outside Diameter:	1.306 Inches Minimum And 1.342 Inches Maximum
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	1.040 Inches Minimum And 1.052 Inches Maximum
End Item Identification:	W/s: Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Mh-53e; Engine, Aircraft, Tf-33-p-7 (c-141a/b); Aircraft, C-2a (reprocured); Support Equipment, B-1 Aircraft; Helicopter, Advance Attack, Ah-1w; Aircraft, T-2; Engine,m Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p)
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-215 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.