

**Description**

Inner diameter: 1.359, thickness: 0.139", preformed packing, hydrocarbon fuel resistant, MS29513 series o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS29513220
Minimum Qty (MOQ):	25
NSN:	5331-00-166-5992
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



## P/N MS29513-220 Specifications

<b>Outside Diameter:</b>	1.637 Inches Nominal
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	1.353 Inches Minimum And 1.365 Inches Maximum
<b>Elongation Percentage:</b>	200 Maximum
<b>Hardness Rating:</b>	65.0 Shore Durometer A Nominal
<b>Criticality Code Justification:</b>	Adyt
<b>Criticality Code Justification:</b>	Zzzw
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr
<b>Departure From Cited Document:</b>	Cleaning, Packaging, And Marking Iaw Mil-std-1330d

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-220](https://military-fasteners.com/o_rings/o_rings/MS29513-220) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.