

P/N MS29513-225

Description

Inner diameter: 1.859, thickness: 0.139", preformed packing o-ring, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS29513225

Minimum Qty (MOQ): 25

NSN: 5331-00-291-7340

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







^{*} See page 2 for technical characteristics

P/N MS29513-225 Specifications

Outside Diameter:	2.111 Inches Minimum And 2.163 Inches Maximum
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	1.849 Inches Minimum And 1.869 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-225 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/MS29513-225 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/MS29513-225 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29513-225 and selecting the quantity you want then click "add to cart".