

## Description

inner diameter: 1.984", thickness 0.139", preformed packing, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS29513226
Minimum Qty (MOQ):	25
NSN:	5331-00-263-5173
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS29513-226 Specifications

<b>Outside Diameter:</b>	2.262 Inches Nominal
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	1.974 Inches Minimum And 1.994 Inches Maximum
<b>Elongation Percentage:</b>	200 Maximum
<b>Hardness Rating:</b>	65.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-226](https://military-fasteners.com/o_rings/o_rings/MS29513-226) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.