

## P/N MS29513-233

### **Description**

inner diameter: 2.859", thickness: 0.139", preformed packing, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513233

Minimum Qty (MOQ): 20

NSN: 5331-00-297-6527

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-233 Specifications

Outside Diameter:	3.105 Inches Minimum And 3.169 Inches Maximum
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	2.844 Inches Minimum And 2.874 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-233">https://military-fasteners.com/o\_rings/o\_rings/MS29513-233</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-233">https://military-fasteners.com/o\_rings/MS29513-233</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-233">https://military-fasteners.com/o\_rings/MS29513-233</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-233">https://military-fasteners.com/o\_rings/MS29513-233</a> and selecting the quantity you want then click "add to cart".