

P/N MS29513-235

Description

inner diameter: 3.109", thickness 0.139", preformed packing o-ring, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information


SKU / Model: MS29513235

Minimum Qty (MOQ): 25

NSN: 5331-00-251-9369

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









P/N MS29513-235 Specifications

Outside Diameter:	3.355 Inches Minimum And 3.419 Inches Maximum
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	3.094 Inches Minimum And 3.124 Inches Maximum
Elongation Percentage:	276 Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-235 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/MS29513-235 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/MS29513-235 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29513-235 and selecting the quantity you want then click "add to cart".