

**Description**




inner diameter: 3.359", thickness 0.139", preformed packing, hydrocarbon fuel resistant, MS29513 series o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS29513237
Minimum Qty (MOQ):	20
NSN:	5331-00-291-3078
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



## P/N MS29513-237 Specifications

<b>Outside Diameter:</b>	3.637 Inches Nominal
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	3.344 Inches Minimum And 3.374 Inches Maximum
<b>Elongation Percentage:</b>	200 Maximum
<b>Hardness Rating:</b>	65.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-237](https://military-fasteners.com/o_rings/o_rings/MS29513-237) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.