

Description

inner diameter: 3.734", thickness 0.139", preformed packing, hydrocarbon fuel resistant, MS29513 series oring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513240
Minimum Qty (MOQ):	25
NSN:	5331-00-291-3070
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N MS29513-240 Specifications

Outside Diameter:	3.976 Inches Minimum And 4.048 Inches Maximum
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	3.719 Inches Minimum And 3.749 Inches Maximum
End Item Identification:	W/s: Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Vehicle, Aircraft Refueler R-14; Systems, Jp-5 Aviation Fuels; Shipboard Material Handling Equipment (mhe); Support Equipment, B-1 Aircraft; Aircraft, Osprey V-22a, Marine Corps; Aircraft, Osprey V-22a, Air Force; Ticonderoga Class Cg (47); Aircraft, C-18a, Ec-18b
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-240 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.