



Military-Fasteners.com

P/N MS29513-247

## Description

inner diameter: 4.609", thickness 0.139", preformed packing, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS29513247
Minimum Qty (MOQ):	25
NSN:	5331-00-291-3311
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS29513-247 Specifications

<b>Outside Diameter:</b>	4.887 Inches Nominal
<b>Temp Rating:</b>	-65.0 Deg Fahrenheit And 200.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	4.594 Inches Minimum And 4.624 Inches Maximum
<b>End Item Identification:</b>	W/s: Ticonderoga Class Cg (47); Aircraft, C-18a, Ec-18b; Support Equipment (se), B-2 Bomber; Forrestal Class Cv; Shipboard Material Handling Equipment; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Systems, Jp-5 Aviation Fuels; Helicopter, Hh-53h Pave Low; Fire Pumps
<b>Elongation Percentage:</b>	200 Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-247](https://military-fasteners.com/o_rings/o_rings/MS29513-247) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.