

# P/N MS29513-254

### **Description**

inner diameter: 5.484", thickness 0.139", preformed packing o-ring - hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513254

Minimum Qty (MOQ): 10

NSN: 5331-00-292-7565

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-254 Specifications

Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	5.461 Inches Minimum And 5.507 Inches Maximum
Hardness Rating:	65.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-254">https://military-fasteners.com/o\_rings/o\_rings/MS29513-254</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-254">https://military-fasteners.com/o\_rings/o\_rings/MS29513-254</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-254">https://military-fasteners.com/o\_rings/o\_rings/MS29513-254</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-254">https://military-fasteners.com/o\_rings/MS29513-254</a> and selecting the quantity you want then click "add to cart".