

Description

inner diameter: 1.475", thickness 0.210", preformed packing, hydrocarbon fuel resistant, MS29513 series o-ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513325
Minimum Qty (MOQ):	25
NSN:	5331-00-265-1096
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N MS29513-325 Specifications

Outside Diameter:	1.895 Inches Nominal
Temp Rating:	-65.0 Deg Fahrenheit And 200.0 Deg Fahrenheit
Cross-sectional Height:	0.205 Inches Minimum And 0.215 Inches Maximum
Center Hole Diameter:	1.465 Inches Minimum And 1.485 Inches Maximum
End Item Identification:	Aircraft, C-2a (reprocured); Nimitz Class Cvn; Helicopter, Sof / Hh-53h Pave Low; Deck Machinery; Aircraft, Sof (Ac-130h, Mc-130h, Ec-130e, Hc-130); Consolidated Targets; Engine, Aircraft, T56-a-7/15 (c-130b/e/h/n/p); Crane (rt41aa); Whidbey Island Class Lsd
Elongation Percentage:	200 Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-325 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.