

P/N MS29513-326

Description

inner diameter: 1.60", thickness 0.21", preformed packing o-ring, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS29513326

Minimum Qty (MOQ): 25

NSN: 5331-00-265-1087

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









^{*} See page 2 for technical characteristics

P/N MS29513-326 Specifications

Outside Diameter:	1.995 Inches Minimum And 2.045 Inches Maximum
Cross-sectional Height:	0.205 Inches Minimum And 0.215 Inches Maximum
Center Hole Diameter:	1.590 Inches Minimum And 1.610 Inches Maximum
End Item Identification:	W/s: Aircraft, Galaxy C-5; Spruance Class Dd (963); Support Equipment, B-1 Aircraft; Systems, Jp-5 Aviation Fuels; Support Equipment, Mx Peacekeeper Missile; Ticonderoga Class Cg (47); Helicopter, Mh-53e; Aircraft, B-2 Bomber (atb); Cvn 68 Class Reactor Fill Auxiliary System; Helicopter, Hh-53h Pave Low
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-326 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.