

## Description

inner diameter: 0.301", thickness 0.07", preformed packing, synthetic lubricant resistant, MS29561 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS29561011                                |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5331-00-542-1421                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS29561-011 Specifications

|                                |   |
|--------------------------------|---|
| <b>Outside Diameter:</b>       | 0.441 Inches Nominal                          |
| <b>Cross-sectional Height:</b> | 0.067 Inches Minimum And 0.073 Inches Maximum |
| <b>Center Hole Diameter:</b>   | 0.296 Inches Minimum And 0.306 Inches Maximum |
| <b>Elongation Percentage:</b>  | 250 Maximum                                   |
| <b>Hardness Rating:</b>        | 70.0 Shore Durometer A Nominal                |
| <b>Material:</b>               | Rubber Butadiene-acrylonitrile Class Nbr      |

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29561-011](https://military-fasteners.com/o_rings/o_rings/MS29561-011) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.