

P/N MS29561-113

Description

inner diameter: 0.549", thickness 0.103", preformed packing, synthetic lubricant resistant

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS29561113

Minimum Qty (MOQ): 25

NSN: 5331-00-585-1065

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



^{*} See page 2 for technical characteristics

P/N MS29561-113 Specifications

Outside Diameter:	0.755 Inches Nominal
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	0.544 Inches Minimum And 0.554 Inches Maximum
Elongation Percentage:	250 Maximum
Hardness Rating:	70.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/MS29561-113 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29561-113 and selecting the quantity you want then click out https://military-fasteners.com/o_rings/MS29561-113 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29561-113 and selecting the quantity you want then click "add to cart".