

Description

inner diameter: 1.674", thickness 0.103", preformed packing o-ring - synthetic lubricant resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29561131
Minimum Qty (MOQ):	10
NSN:	5331-00-800-6351
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS29561-131 Specifications

<b>Outside Diameter:</b>	1.880 Inches Nominal
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	1.659 Inches Minimum And 1.689 Inches Maximum
<b>Elongation Percentage:</b>	250 Maximum
<b>Hardness Rating:</b>	70.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29561-131](https://military-fasteners.com/o_rings/o_rings/MS29561-131) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.