

P/N MS29561-213

Description

inner diameter: 0.921", thickness 0.139", preformed packing, synthetic lubricant resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS29561213

Minimum Qty (MOQ): 20

NSN: 5331-00-702-4715

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







^{*} See page 2 for technical characteristics

P/N MS29561-213 Specifications

Outside Diameter:	1.199 Inches Nominal
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	0.915 Inches Minimum And 0.927 Inches Maximum
Elongation Percentage:	250 Maximum
Hardness Rating:	70.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29561-213 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/MS29561-213 and selecting the quantity you want then click out https://military-fasteners.com/o_rings/o_rings/MS29561-213 and selecting the quantity you want then click out https://military-fasteners.com/o_rings/o_rings/MS29561-213 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29561-213 and selecting the quantity you want then click "add to cart".