

**Description**

Inner diameter: 1.046", thickness 0.139", preformed packing o-ring - synthetic lubricant resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS29561215                                |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5331-00-803-9886                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



## P/N MS29561-215 Specifications

|                                |   |
|--------------------------------|---|
| <b>Outside Diameter:</b>       | 1.324 Inches Nominal                          |
| <b>Cross-sectional Height:</b> | 0.135 Inches Minimum And 0.143 Inches Maximum |
| <b>Center Hole Diameter:</b>   | 1.040 Inches Minimum And 1.052 Inches Maximum |
| <b>Elongation Percentage:</b>  | 250 Maximum                                   |
| <b>Hardness Rating:</b>        | 70.0 Shore Durometer A Nominal                |
| <b>Material:</b>               | Rubber Butadiene-acrylonitrile Class Nbr      |

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29561-215](https://military-fasteners.com/o_rings/o_rings/MS29561-215) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.