

**Description**

inner diameter: 1.296", thickness 0.139", preformed packing o-ring - synthetic lubricant resistant"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS29561219
Minimum Qty (MOQ):	10
NSN:	5331-00-807-7931
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE  
AVAILABLE

## P/N MS29561-219 Specifications

<b>Outside Diameter:</b>	1.574 Inches Nominal
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	1.290 Inches Minimum And 1.302 Inches Maximum
<b>Elongation Percentage:</b>	250 Maximum
<b>Hardness Rating:</b>	70.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29561-219](https://military-fasteners.com/o_rings/o_rings/MS29561-219) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.