

Description

inner diameter: 4.734", thickness 0.139", preformed packing o-ring - synthetic lubricant resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS29561244 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5331-00-585-1069 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



* See page 2 for technical characteristics

P/N MS29561-244 Specifications

| | |
|--------------------------------|---|
| Outside Diameter: | 4.512 Inches Nominal |
| Cross-sectional Height: | 0.135 Inches Minimum And 0.143 Inches Maximum |
| Center Hole Diameter: | 4.219 Inches Minimum And 4.249 Inches Maximum |
| Elongation Percentage: | 250 Maximum |
| Hardness Rating: | 70.0 Shore Durometer A Nominal |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr |

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29561-244 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.