

**Description**

Fastener Length: 19/64", Thread: 6-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS321212L
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-161-0343
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS3212-12L Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.248 Inches Minimum And 0.312 Inches Maximum
<b>Fastener Length:</b>	0.292 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Watertight
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.294 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Features Provided:</b>	O Ring
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	Qq-s-763 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-12L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.