



Military-Fasteners.com

P/N MS3212-19

Description

Fastener Length: 7/8", Thread: 6-32, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS321219
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-953-4502
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N MS3212-19 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.782 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.256 Inches Minimum And 0.294 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.