

P/N MS3212-22

Description

Fastener Length: 5/16", Thread: 8-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS321222

Minimum Qty (MOQ): 25

NSN: 5305-00-245-4621

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS3212-22 Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.219 Inches Minimum And 0.312 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Watertight |
| Head Diameter: | 0.306 Inches Minimum And 0.347 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Features Provided: | O Ring |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel Comp 304 Or Steel Comp 305 |
| Screw Material Document And Classification: | Aisi 304 305 Fed Spec All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS3212-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.