

P/N MS3212-23

Description

Fastener Length: 3/8", Thread: 8-32, Thread Length: 3/8", MS3212 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS321223

Minimum Qty (MOQ): 20

NSN: 5305-00-488-6512

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS3212-23 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.282 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.306 Inches Minimum And 0.347 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 304 Or Steel Comp 305
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS3212-23 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.