

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 7/16", pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS321224
Minimum Qty (MOQ):	20
NSN:	5305-01-321-2195
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS3212-24 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.356 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.418 Inches Minimum And 0.438 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.308 Inches Minimum And 0.347 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp Xm-7
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.