

**Description**

Fastener Length: 3/4", Thread: 8-32, Thread Length: 23/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS321228L
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-326-2824
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS3212-28L Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.658 Inches Minimum And 0.720 Inches Maximum
<b>Fastener Length:</b>	0.720 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Watertight
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.347 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Locking Feature:</b>	Patch Or Pellet Or Strip
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Features Provided:</b>	O Ring
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp Xm-7
<b>Locking Feature Material:</b>	Plastic Polyamide
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-28L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.