

**Description**

Fastener Length: 3/8", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS321231L
Minimum Qty (MOQ):	10
NSN:	5305-01-130-6559
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS3212-31L Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	0.355 Inches Minimum And 0.375 Inches Maximum
<b>Head Style:</b>	Watertight
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.403 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Special Features:</b>	Undercut Head With One O-ring
<b>Material:</b>	Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-31L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.