

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS321231L |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-130-6559 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS3212-31L Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.355 Inches Minimum And 0.375 Inches Maximum |
| Head Style: | Watertight |
| Head Diameter: | 0.357 Inches Minimum And 0.403 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Special Features: | Undercut Head With One O-ring |
| Material: | Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-31L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.