

**Description**

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS321236L
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-269-6263
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS3212-36L Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.658 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.720 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Watertight
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.403 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Features Provided:</b>	O Ring
<b>Thread Quantity Per Inch:</b>	32
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Rubber Silicone Class Q Ring
<b>Material:</b>	Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
<b>Material Document And Classification:</b>	Mil-s-82496 Mil Spec Single Material Response Ring
<b>Surface Treatment:</b>	Passivate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screwseal from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-36L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.