

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS321236L
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-269-6263
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS3212-36L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.658 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.357 Inches Minimum And 0.403 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	32
Material:	Plastic Locking Feature
Material:	Rubber Silicone Class Q Ring
Material:	Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
Material Document And Classification:	Mil-s-82496 Mil Spec Single Material Response Ring
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf

How to Order

Order this screwseal from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-36L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.