

Description

Fastener Length: 3/8", Thread: 10-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS321239
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-085-4056
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS3212-39 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.261 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.357 Inches Minimum And 0.403 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	24
Screw Material:	Steel Comp 304 Or Steel Comp 305
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screwseal from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.