

Description

Fastener Length: 3/8", Thread: 10-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS321239 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-085-4056 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS3212-39 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.261 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.344 Inches Minimum And 0.375 Inches Maximum |
| Head Style: | Watertight |
| Head Diameter: | 0.357 Inches Minimum And 0.403 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Features Provided: | O Ring |
| Thread Quantity Per Inch: | 24 |
| Screw Material: | Steel Comp 304 Or Steel Comp 305 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this screwseal from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.