

## Description

Fastener Length: 3/8", Thread: 10-24, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS321239
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-085-4056
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS3212-39 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.261 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	0.344 Inches Minimum And 0.375 Inches Maximum
<b>Head Style:</b>	Watertight
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.403 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Features Provided:</b>	O Ring
<b>Thread Quantity Per Inch:</b>	24
<b>Screw Material:</b>	Steel Comp 304 Or Steel Comp 305
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screwseal from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.