

P/N MS3212-4

Description

Fastener Length: 7/16", Thread: 4-40, Thread Length: 7/16", pan head, seal type

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information


SKU / Model: MS32124

Minimum Qty (MOQ): 25

NSN: 5305-00-965-5944

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS3212-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.357 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.205 Inches Minimum And 0.238 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	40
Screw Material:	Steel Comp 304 Or Steel Comp 305
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS3212-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS3212-4 and selecting the quantity you