

P/N MS3212-47

Description

Fastener Length: 3/8", Thread: 1/4-20, Thread Length: 3/8", pan head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS321247

Minimum Qty (MOQ): 20

NSN: 5305-00-052-4048

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS3212-47 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.244 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.473 Inches Minimum And 0.517 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Features Provided:	O Ring
Thread Quantity Per Inch:	20
Screw Material:	Steel Comp 304 Or Steel Comp 305
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS3212-47 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.