

**Description**

Fastener Length: 3/4", Thread: 4-40, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS32128
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-993-9268
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS3212-8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.669 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.719 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Watertight
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.238 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Screw Material:</b>	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 302b Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 384 Or Steel Comp 385
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Special Features:</b>	Furnished With One Silicone Rubber O Ring
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this pan head screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3212-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.