

## P/N MS3213-11

## **Description**

Fastener Length: 15/64", Thread: 6-32, Thread Length: 11/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS321311

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-054-2488

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS3213-11 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.168 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.230 Inches Minimum And 0.250 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.256 Inches Minimum And 0.294 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp Xm-7
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Furnished With One 0-ring
Thread Series Designator:	Unc

### **How to Order**

Order this screwseal from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS3213-11">https://military-fasteners.com/screws/machine+screws/MS3213-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.