

Description

Fastener Length: 19/32", Thread: 6-32, Thread Length: 35/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS321317 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-01-031-1425 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS3213-17 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.532 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.594 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Watertight |
| Head Diameter: | 0.256 Inches Minimum And 0.294 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Features Provided: | O Ring |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 75000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 304 Or Steel Comp 305 |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3213-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.