

P/N MS3213-18

Description

Fastener Length: 23/32", Thread: 6-32, Thread Length: 43/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS321318

Minimum Qty (MOQ): 50 EA

NSN: 5305-00-455-0343

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS3213-18 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.657 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.256 Inches Minimum And 0.294 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 304 Or Steel Comp 305 Or Steel
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Furnished W/one Flourosilicone Rubber O-ring Per Mil-r-25988
Thread Series Designator:	Unc

How to Order

Order this screwseal from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS3213-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.