

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS32131L
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-233-3917
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS3213-1L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Maximum
Fastener Length:	0.250 Inches Nominal
Head Style:	Pan No. 2
Head Diameter:	0.205 Inches Minimum And 0.238 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Special Features:	Annular Recess Head With Sealing O-ring,resist To Hydraulic Fluid
Material:	Steel Corrosion Resisting Fastener
Material Document And Classification:	Mil-s-82496 Mil Spec 1st Material Response Overall
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3213-1L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.