

Description

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS32132 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-00-607-0197 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS3213-2 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.231 Inches Minimum And 0.312 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Watertight |
| Head Diameter: | 0.205 Inches Minimum And 0.238 Inches Maximum |
| Head Height: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 75000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel |
| Screw Surface Treatment: | Passivate |
| Special Features: | Furnished With Onerubber O-ring |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3213-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.