

## P/N MS3213-22L

### **Description**

Fastener Length: 5/16", Thread: 8-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS321322L

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-352-2836

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS3213-22L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Nominal
Fastener Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.347 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Locking Feature:	Patch Or Pellet Or Strip
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Locking Feature Material:	Plastic Polyamide
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

## **How to Order**

Order this screwseal from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS3213-22L">https://military-fasteners.com/screws/machine+screws/MS3213-22L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.