

P/N MS3213-25

Military-Fasteners.com

#### Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS321325
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-031-5091
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS3213-25 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.306 Inches Minimum And 0.347 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	75000 Pounds Per Square Inch
Screw Material:	Steel Comp 304 Or Steel Comp 305
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Furnished Lith One O-ring
Thread Series Designator:	Unc

## How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS3213-25</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.