

Description

Fastener Length: 3/8", Thread: 4-40, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS32133
Minimum Qty (MOQ):	25
NSN:	5305-01-049-0010
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS3213-3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.305 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.355 Inches Minimum And 0.375 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.205 Inches Minimum And 0.238 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS3213-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.