

## P/N MS3213-36

## **Description**

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS321336

Minimum Qty (MOQ): 50

NSN: 5305-00-148-1286

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS3213-36 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.657 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Watertight
Head Diameter:	0.357 Inches Minimum And 0.403 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 304 Or Steel Comp 305
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Furnished With One Fluorosilicone Rubber O Ring Per Mil-r-25988
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS3213-36">https://military-fasteners.com/screws/machine+screws/MS3213-36</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.