

Description

MS3217 series oring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS32171050
Minimum Qty (MOQ):	25
NSN:	5325-01-046-3670
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS3217-1050 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.450 Inches Minimum And 0.465 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.048 Inches Minimum And 0.052 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	67.5 Rockwell Superficial 30-n Minimum And 72.0 Rockwell Superficial 30-n Maximum
Material:	Steel,fed Std 66,comp 1066 Thru 1090
Material:	Steel,fed Std 66,comp 1066 Thru 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

How to Order

Order this o-ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS3217-1050> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.