

**Description**

panel thickness 0.250", thread: 6-32, brass, MS33737 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS3373713C
Minimum Qty (MOQ):	10
NSN:	5310-00-875-9664
ECCN:	EAR99
National Motor Freight:	093460, Bolts / Nuts Noi Bbc / Zinc



\* See page 2 for technical characteristics

## P/N MS33737-13C Specifications

<b>Material Thickness:</b>	0.002 Inches Minimum And 0.022 Inches Maximum
<b>Mating Member Diameter Accommodated:</b>	0.138 Inches Nominal
<b>Nut Style:</b>	Sheet Spring
<b>Nut Length:</b>	0.661 Inches Minimum And 0.681 Inches Maximum
<b>Nut Height:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Nut Width:</b>	0.271 Inches Minimum And 0.291 Inches Maximum
<b>Panel Thickness:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Nut Mounting Provision:</b>	Gripping Prongs
<b>Gripping Prong Quantity:</b>	2
<b>Gripping Prong Length:</b>	0.272 Inches Minimum And 0.292 Inches Maximum
<b>Material:</b>	Copper Alloy Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Zinc Overall And Chromate Overall Or Zinc Overall And Phosphate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 1,class 2 Fed Spec 1st Treatment Response Overall Or Qq-z-325 Fed Spec 2nd Treatment Response Overall Or Qq-z-325 Fed Spec 3rd Treatment Response Overall Or Qq-z-325 Fed Spec 4th Treatment Response Overall Or Qq-z-325 Fed Spec 5th Treatment Response Overall

## How to Order

Order this sheet spring nut from our inventory online by visiting <https://military-fasteners.com/nuts/sheet+spring+nuts/MS33737-13C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.