

Description


panel thickness 0.375", thread: 6-32, brass, clip, MS33737 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3373715C
Minimum Qty (MOQ):	10
NSN:	5310-01-420-7611
Schedule B:	7415.33.8010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS33737-15C Specifications

Material Thickness:	0.012 Inches Nominal
Mating Member Diameter Accommodated:	0.138 Inches Nominal
Nut Style:	Sheet Spring
Nut Length:	0.661 Inches Minimum And 0.681 Inches Maximum
Nut Height:	0.740 Inches Minimum And 0.760 Inches Maximum
Nut Width:	0.271 Inches Minimum And 0.291 Inches Maximum
Panel Thickness:	0.365 Inches Minimum And 0.385 Inches Maximum
Material:	Copper Alloy 260 Nut
Material:	Copper Alloy 510 Shell Or Copper Alloy 524 Shell Or Copper Alloy 544 Shell
Material Document And Classification:	Astm B139 Assn Std Single Material Response Shell
Material Document And Classification:	Astm B36 Assn Std Single Material Response Nut
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty2, Cl2 Fed Spec Single Treatment Response Overall

How to Order

Order this sheet spring nut from our inventory online by visiting <https://military-fasteners.com/nuts/sheet+spring+nuts/MS33737-15C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.