

**Description**

MS3476 series connector

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS3476L1210P
Minimum Qty (MOQ):	1
NSN:	5935-00-468-2561
Schedule B:	8535.90.8040
ECCN:	9A991
National Motor Freight:	061680, Elec Wiring Plugs Etc



\* See page 2 for technical characteristics

# P/N MS3476L12-10P Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Body Style:	Straight Shape, Internal Coupling
Overall Length:	1.420 Inches Maximum
Overall Diameter:	1.043 Inches Maximum
Environmental Protection:	Moisture Resistant And Salt Water Resistant And Vibration Resistant
Threaded Device Type:	Back Shell
Mating End Quantity:	1
Contact Position Arrangement Style:	10-dec Single Mating End
Contact Position Arrangement Style:	12-10 Single Mating End
Contact Removability:	Removable Single Mating End Single Contact Grouping
Contact Maximum Ac Voltage Rating In Volts:	600.0 Single Mating End Single Contact Grouping
Polarization Method:	Keyway Or Multiple Keyway
Insert Position In Deg:	0.0
Shell Type:	Solid
Connector Locking Method:	Bayonet Latch
Nominal Thread Length:	0.290 Inches
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.750 Inches
Terminal Location:	Back Single Mating End Single Contact Grouping
Contact Surface Treatment:	Gold Single Mating End Single Contact Grouping And Nickel Single Mating End Single Contact Grouping
Contact Surface Treatment Document And Classification:	Mil-g-45204 Ty 1,1,grade C Mil Spec 1st Treatment Response Single Mating End Single Contact Grouping And Qq-n-290 Grade E Fed Spec 2nd Treatment Response Single Mating End Single Contact Grouping
Terminal Type:	Crimp Single Mating End Single Contact Grouping
Shell Material:	Aluminum Alloy
Shell Surface Treatment:	Nickel
Shell Surface Treatment Document And Classification:	Mil-c-26074 Cl 3,grade B Mil Spec Single Treatment Response
Included Contact Quantity:	10 Single Mating End Single Contact Grouping
Included Contact Type:	Round Pin Single Mating End Single Contact Grouping
Precious Material And Location:	Contact Surfaces Gold

<b>Precious Material And Weight:</b>	0.050 Gold Grains, Troy
<b>Precious Material:</b>	Gold
<b>Test Data Document:</b>	81349-mil-c-26482 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
<b>Thread Series Designator:</b>	Unef
<b>Specification/standard Data:</b>	96906-ms3476 Government Standard

## How to Order

Order this electrical connector plug from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+connector+plugs/MS3476L12-10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.